

RX8

8 inch Coaxial Loudspeaker



Overview

The RX8 is a high-efficiency, high-fidelity coaxial loudspeaker that provides output capability typical of a much larger loudspeaker. The transducer's high efficiency and horn-loaded HF compression driver give the RX8 a surprisingly high output-to-size ratio, and its broad 90° x 75° coverage is particularly effective in close quarters. The RX8's compact, horizontal enclosure may be mounted close to walls or ceilings, under balconies, or along a stage front with minimal effect on sight lines. Its small size also allows it to be readily concealed within a venue's architecture when the loudspeaker must be hidden from view. An assortment of M6 and VESA points facilitate installation with an optional Fulcrum UB-RX8 yoke bracket or third-party mounting solutions.

Fulcrum Acoustic's **TQ™** processing is an integral part of the RX8 design. Sound, innovative acoustical design combined with state of the art digital processing leads to exceptional clarity and precise transient response, even at very high sound pressure levels. The required digital signal processing can be provided by one of many supported platforms.

The RX8 is an excellent option any time moderately high SPLs are required but limited space is available. Spoken word sounds very natural, and the coaxial design assures that this remains so even off-axis. Low frequency extension to 82 Hz enables it to integrate well with subwoofers for full range music reproduction. The RX8 is a perfect choice for delay fill, background music, and speech reproduction systems, which makes it ideal for houses of worship, theaters, restaurants, nightclubs, museum kiosks, theme parks, and more.

Performance Specifications¹

Operating Mode

Single-amplified w/ DSP

Operating Range²

82 Hz to 20 kHz

Nominal Beamwidth (rotatable)

90° x 75°

Transducers

HF/LF: Coaxial 1.0 inch diaphragm compression driver, neodymium magnet; 8.0 inch woofer, 2.0 inch voice coil, ceramic magnet

Power Handling @ Nominal Impedance³

57 V / 200 W @ 16 Ω

Nominal Sensitivity @ Input Voltage⁴ (whole space)

102 dB @ 4.00 V

Nominal Maximum SPL (peak / continuous)

131 dB / 125 dB

Equalized Sensitivity @ Input Voltage⁵

93 dB @ 4.00 V

Equalized Maximum SPL⁶ (peak / continuous)

122 dB / 116 dB

AES75 Maximum Linear Sound Levels⁷

107.3 dBZ / 124.4 dBZpk / 104.0 dBA
at an RMS input level of 26.4 dBV (20.9 V)

Recommended Power Amplifier

200 W to 400 W @ 16 Ω

Physical Specifications

Connections

(2) Neutrik NL4 Speakon

Pin 1+/-: Full Range Pin 2+/-: No Connection

Mounting / Suspension Points

(2) M6 x 1.0 yoke points, (2) M6 x 1.0 rear points,

(4) M4 x 0.7 VESA 75 x 75 mm points

Dimensions / Weight

See pages 5 & 6

Finish

Black painted enclosure w/ matte black grille, or

White painted enclosure w/ matte white grille

Options


UB-RX8 yoke bracket, Phoenix block input, Custom color finish,
IP55 Weather-resistant (WR) enclosure & hardware,
70 V multi-tap transformer (RX8-MT60)




fulcrum
ACOUSTIC®

product specification


Axial Sensitivity (dB SPL, 4.00 V @ 1 m)^{8,9}




Horizontal Off Axis Response^{8,12}




Axial Processed Response (dB)^{8,10}




Vertical Off Axis Response^{8,12}




Axial Processed Phase Response (degrees)^{8,11}




Beamwidth^{8,13}




Impedance (ohms)




Directivity Index (dB)¹⁴



Horizontal Polar Response (30 dB Scale, 6 dB per Major Division)




Vertical Polar Response (30 dB Scale, 6 dB per Major Division)




Connections


Neutrik NL4 Speakon Input



Optional Phoenix Input



Optional -MT60 70 V Input



Note: Phoenix blocks accept minimum 24 AWG / 0.2 mm², maximum 16 AWG / 1.5 mm² cable

Mechanical Specification Drawings

2D and 3D DWG dimensional drawings are available for download at www.fulcrum-acoustic.com/resources

Notes

- ¹ **Performance Specifications** All acoustic specifications rounded to nearest whole number. External DSP with Fulcrum Acoustic-provided settings is required to achieve the specified performance.
- ² **Operating Range** The frequency range within which the processed response is within 10 dB of the average.
- ³ **Power Handling** Based on the AES power handling of the transducers.
- ⁴ **Nominal Sensitivity** The 1-meter-referenced SPL produced by a 1 watt band limited pink noise signal, with no processing applied.
- ⁵ **Equalized Sensitivity** The 1-meter-referenced SPL produced when an EIA-426-B signal is applied to an equalized loudspeaker system, at a level which produces a total power of 1 watt, in sum, to the loudspeaker subsections.
- ⁶ **Equalized Maximum SPL** The 1-meter-referenced SPL produced when an EIA-426-B signal is applied to an equalized loudspeaker system, at a level which drives at least one subsection to its rated power.
- ⁷ **AES75 Maximum Linear Sound Levels** Per AES75-2023: "AES standard for acoustics – Measuring loudspeaker maximum linear sound levels using noise".
- ⁸ **Resolution** All response graphs are subjected to 1/6 octave cepstral smoothing with a gaussian weighting function.
- ⁹ **Axial Sensitivity** The SPL plotted against frequency for a 1 watt swept sine wave, referenced to 1 m with no signal processing.
- ¹⁰ **Axial Processed Response** The axial magnitude response with recommended signal processing applied.
- ¹¹ **Axial Processed Phase Response** The axial phase response with recommended signal processing applied, and latency removed.
- ¹² **Horizontal / Vertical Off Axis Responses** The magnitude response at various angles off axis, with recommended signal processing applied.
- ¹³ **Beamwidth** The angle between the -6 dB points in a loudspeaker's polar response.
- ¹⁴ **Directivity Index (Di)** The ratio of the on-axis sound pressure squared to the spherical average of the sound pressure squared at a particular frequency expressed in dB. To convert the directivity index to directivity factor (Q) use the formula $10^{Di/10}$.



fulcrum
ACOUSTIC®


product specification

Notes:


1. Net Weight = Approx. 14.0 lb / 6.4 kg
2. Symbol  = M6 x 1.0 nut plate
3. Symbol  = M4 x 0.7 T-nut
4. Symbol  = CoG
5. Enclosure construction: PVC

REVISIONS

REV	DESCRIPTION	APPR / DATE
1	NEW ISSUE	RAF 04/30/24
2	UPDATE NOTES, GRILLE	RAF 02/26/26



THIRD ANGLE PROJECTION



THIS DRAWING IS THE PROPERTY OF FULCRUM ACOUSTIC, AND SHALL NOT BE COPIED, REPRODUCED, OR USED AS THE BASIS FOR MANUFACTURE OR SALE OF APPARATUS WITHOUT WRITTEN AUTHORIZATION. DO NOT SCALE DRAWING.

UNLESS OTHERWISE SPECIFIED:
ALL DIMENSIONS ARE IN INCHES

TOLERANCE IN INCHES
.X±.1 .XX±.015 .XXX±.005
FRACTIONS 1/32
ANGLES ±1/2°

(X.XX) = REF DIMS NO TOLERANCE IMPLIED

TSC = THEORETICAL SHARP CORNER

DIMENSIONS ACROSS CENTERLINES
TO BE SYMMETRICAL

STATUS RELEASED

APPROVALS

DRAWN: RAF 04/30/24

CHECKED: DEW 04/30/24

DES' ENG:

MFG' ENG:



FULCRUM ACOUSTIC, LLC
1 MAIN STREET, WHITINSVILLE, MA 01588 USA

TITLE: Mechanical Spec,
RX8

A SHEET 1 OF 1 SCALE: 1:8
DWG. NO. 820-100-173 REV 2

Drawing is reduced. Do not scale.



fulcrum
ACOUSTIC®


product specification, weather-resistant (WR) version

Notes:


1. Net Weight = Approx. 15.0 lb / 6.8 kg
2. Symbol = M6 x 1.0 nut plate
3. Symbol = M4 x 0.7 T-nut
4. Symbol = CoG
5. Enclosure construction: PVC
6. Includes gland nut & 3 meter 16 AWG / 1.5 mm² tail

REVISIONS

REV	DESCRIPTION	APPR / DATE
1	NEW ISSUE	RAF 04/30/24
2	UPDATE NOTES, GRILLE	RAF 02/26/26



THIRD ANGLE PROJECTION



THIS DRAWING IS THE PROPERTY OF FULCRUM ACOUSTIC, AND SHALL NOT BE COPIED, REPRODUCED, OR USED AS THE BASIS FOR MANUFACTURE OR SALE OF APPARATUS WITHOUT WRITTEN AUTHORIZATION. DO NOT SCALE DRAWING.

UNLESS OTHERWISE SPECIFIED:
ALL DIMENSIONS ARE IN INCHES

TOLERANCE IN INCHES
.XX±.015 .XXX±.005
FRACTIONS 1/32
ANGLES ±1/2°

(X.XX) = REF DIMS NO TOLERANCE IMPLIED

TSC = THEORETICAL SHARP CORNER

DIMENSIONS ACROSS CENTERLINES
TO BE SYMMETRICAL

STATUS RELEASED

APPROVALS	DATE
DRAWN: RAF	04/30/24
CHECKED: DEW	04/30/24
DES ENG:	
MFG ENG:	



FULCRUM ACOUSTIC, LLC
1 MAIN STREET, WHITINSVILLE, MA 01588 USA

TITLE: Mechanical Spec,
RX8-WR

A SHEET 1 OF 1 SCALE: 1:8
DWG. NO. 820-100-177 REV 2

Drawing is reduced. Do not scale.






fulcrum
ACOUSTIC®

optional accessory

Notes:

1. Net Weight = Approx. 2.0 lb / 0.9 kg
2. Material: 10 GA (0.135") CRS, weather-resistant coating
3. Includes 2x each M6 socket head cap screws, split washers, flat washers

REVISIONS		
REV	DESCRIPTION	APPR / DATE
1	NEW ISSUE	RAF 04/30/24



THIRD ANGLE PROJECTION THIS DRAWING IS THE PROPERTY OF FULCRUM ACOUSTIC, AND SHALL NOT BE COPIED, REPRODUCED, OR USED AS THE BASIS FOR MANUFACTURE OR SALE OF APPARATUS WITHOUT WRITTEN AUTHORIZATION. DO NOT SCALE DRAWING.	UNLESS OTHERWISE SPECIFIED: ALL DIMENSIONS ARE IN INCHES TOLERANCE IN INCHES .X±.1 .XX±.015 .XXX±.005 FRACTIONS ±1/32 ANGLES ±1/2° (X.XX) = REF DIMS NO TOLERANCE IMPLIED TSC = THEORETICAL SHARP CORNER DIMENSIONS ACROSS CENTERLINES TO BE SYMMETRICAL	STATUS RELEASED		FULCRUM ACOUSTIC, LLC 670 LINWOOD AVE., LINWOOD, MA 01925 USA	
		APPROVALS	DATE	TITLE: Mechanical Spec, UB-RX8 Yoke Bracket	
		DRAWN: RAF	04/30/24	A SHEET 1 OF 1 SCALE: 1:8	
		CHECKED: DEW	04/30/24	DWG. NO. 820-300-057 REV 1	

Drawing is reduced. Do not scale.